

Sigma Fine (Piezo) Stages (high stiffness type) XY Piezo Stages Aperture Type

SFS-H

SFS-120XY(WA)



Nanometer resolution high stiffness flexure stages.

SFS-H




- These compact piezo stages offer high precision and high resolution positioning by utilizing full closed loop control with digital frequency based sensors.
- Using piezo element actuators, open loop travel between 90µm – 100µm is available, with minimum incremental motion as small as 1nm. Compared to the open-loop control, the maximum travel of closed-loop control will be less about 10%.
- Closed loop travel is 80% of the open loop maximum and closed loop resolution is 10nm.
- Recommended controllers are the FINE series controllers. [Reference](#) G129 Both digital and analog inputs are available.




Outline Drawing


SFS-H40X(CL) Hexagon socket head cap screw M3×10...2 screws




SFS-H40Z(CL) Hexagon socket head cap screw M3×10...2 screws



SFS-H60X(CL) Hexagon socket head cap screw M4×10...4 screws



SFS-H60XY(CL) Hexagon socket head cap screw M4×10...4 screws



Specifications

Part Number	SFS-H40X(CL)	SFS-H40Z(CL)	SFS-H60X(CL)	SFS-H60XY(CL)
Travel (at open-loop control)	90µm±15%	100µm±15%	100µm±15%	100µm±15%
Stage Size [mm]	40×40	40×40	60×60	60×60
Actuator	Piezo actuator	Piezo actuator	Piezo actuator	Piezo actuator
Weight [kg]	0.28	0.28	0.4	0.43
Theoretical Resolution (open-loop) [nm]	1	1	1	1
Resolution (closed-loop) [nm]	10	10	10	10
Linearity [%]	0.3 or lower	0.3 or lower	0.3 or lower	0.3 or lower
Perpendicularity (Horizontal Direction) [µm]	1	1	1	1
Positional Repeatability [µm]	0.1 or lower	0.1 or lower	0.1 or lower	0.1 or lower
Load Capacity [N]	9.8 (1.0kgf)	6.7 (0.7kgf)	19.6 (2.0kgf)	14.7 (1.5kgf)
Micro-displacement Sensor	Digital Sensor	Digital Sensor	Digital Sensor	Digital Sensor
Compatible Cable	Attached cable (2m)	Attached cable (2m)	FINE-CA-3: For piezo DS1-CA-3: For digital sensor	FINE-CA-3: For piezo DS1-CA-3: For digital sensor

Application Systems
Optics & Optical Coatings
Opto-Mechanics
Bases
Manual Stages
Actuators & Adjusters

Motorized Stages

Light Sources & Laser Safety

Index

Guide

Controllers/Drivers

Softwares

Stepping Motor

AC Servo Motor

Cables

Piezo

X Translation

Theta Rotation

Goniometer

Vacuum

Options

40 × 40 mm

60 × 60 mm

80 × 80 mm

85 × 85 mm

100 × 100 mm


120 × 120 mm

Others




Outline Drawing

SFS-H60Z(CL) Hexagon socket head cap screw M4x10...4 screws




SFS-H60XYZ(CL) Hexagon socket head cap screw M4x10...4 screws



SFS-120XY(WA)


Two Axis Nanometer resolution high stiffness flexure stages with central aperture.

- High precision XY piezo stages offer high precision and high resolution positioning by utilizing full closed loop control with digital frequency based sensors.
- 50mm x 50mm aperture makes these stages ideal for microscopy applications
- Using piezo element actuators, open loop travel between 90µm – 100µm is available, with minimum incremental motion as small as 1nm.
- Closed loop travel is 80% of the open loop maximum and closed loop resolution is 10nm.
- Recommended controller is the FINE-503(**). [WEB Reference](#) [Catalog Code](#) W9057



Outline Drawing

SFS-120XY(WA) Hexagon socket head cap screw M4x8...4 screws



Specifications

Part Number	SFS-H60Z(CL)	SFS-H60XYZ(CL)	SFS-120XY(WA)
Travel (at open-loop control)	100µm±15%	100µm±15%	100µm±10%
Stage Size [mm]	60x60	60x60	120x120
Actuator	Piezo actuator	Piezo actuator	Piezo actuator
Weight [kg]	0.33	0.63	1.2
Theoretical Resolution (open-loop) [nm]	1	1	1
Resolution (closed-loop) [nm]	10	10	10
Linearity [%]	0.3 or lower	0.5 or lower	—
Perpendicularity (Horizontal Direction) [µm]	1	1	1 or lower
Positional Repeatability [µm]	0.1 or lower	0.15 or lower	0.1 or lower
Load Capacity [N]	9.8 (1.0kgf)	9.8 (1.0kgf)	19.6 (2.0kgf)
Micro-displacement Sensor	Digital sensor	Digital sensor	Digital sensor
Compatible Cable	FINE-CA-3: For piezo DS1-CA-3: For digital sensor	FINE-CA-3: For piezo DS1-CA-3: For digital sensor	FINE-CA-3: For piezo DS1-CA-3: For digital sensor

Application Systems

Optics & Optical Coatings

Opto-Mechanics

Bases

Manual Stages

Actuators & Adjusters

MotORIZED Stages

Light Sources & Laser Safety

Index

Guide

Controllers/Drivers

Softwares

Stepping Motor

AC Servo Motor

Cables

Piezo

X Translation

Theta Rotation

Goniometer

Vacuum

Options

40 x 40 mm

60 x 60 mm

80 x 80 mm

85 x 85 mm

100 x 100 mm

120 x 120 mm

Others