RR/DR




Accessories for mirror holders and lens holders.




Outline Drawing

tighten the retaining rings.

sets of five.





• Retaining rings and Resin rings are sold seperately in

• The retaining ring spanner wrench (NRS) is used to

Attention

rings for beamsplitter holders.

Guide

We cannot guarantee our retaining rings will fit into non Opto-Sigma threaded holes.

▶ Please contact our Sales Division regarding tapered retaining

Retaining F	ling			Primary materi Finish: Black A	
Part Number	Quantity [Pieces]	Outer Diameter ϕ A [mm]	Inner Diameter \$\phi B\$ [mm]	Thickness C [mm]	Screw Pitch [mm]
RR-10-5	5	ϕ 10.85	φ7	3	0.75
RR-12.7-5	5	ϕ 13.55	ϕ 9.7	3	0.75
RR-15-5	5	ϕ 15.85	φ12	3	0.75
RR-20-5	5	ϕ 20.85	φ17	3	0.75
RR-25-5	5	φ25.85	φ22	3	0.75
RR-25.4-5	5	φ26.25	φ22	3	0.75
RR-30-5	5	ϕ 30.85	φ27	3	0.75
RR-38.1-5	5	ϕ 38.95	φ35	3	0.75
RR-40-5	5	ϕ 40.85	φ37	3	0.75
RR-50-5	5	ϕ 50.85	φ46	3	0.75
RR-50.8-5	5	φ51.65	φ47	3	0.75
RR-52-5	5	φ52.85	φ48	3	0.75
RR-60-5	5	ϕ 60.85	φ56	3	0.75
RR-80-5	5	φ81.1	φ75	3.5	1
RR-100-5	5	φ101.1	φ95	4	1
RR-130-5	5	φ131.1	φ124	4	1
RR-150-5	5	φ151.1	φ144	4	1

Resin King	Finish: None			
Part Number	Quantity [Pieces]	Outer Diameter ϕ D [mm]	Inner Diameter	Thickness F [mm]
DR-10-5	5	φ10	φ7	1
DR-12.7-5	5	φ12.7	φ9.7	1
DR-15-5	5	φ15	φ12	1
DR-20-5	5	φ20	φ17	1
DR-25-5	5	φ25	φ22	1
DR-25.4-5	5	φ25.4	φ22	1
DR-30-5	5	φ30	φ27	1
DR-38.1-5	5	φ38.1	φ35	1
DR-40-5	5	φ40	φ37	1
DR-50-5	5	φ50	φ46	1
DR-50.8-5	5	ϕ 50.8	φ47	1
DR-52-5	5	φ52	φ48	1
DR-60-5	5	φ60	φ56	1
DR-80-5	5	φ80	φ75	1.5
DR-100-5	5	φ100	φ95	1.5
DR-130-5	5	φ130	φ124	2
DR-150-5	5	φ150	φ144	2

NRS




Spanner wrenches can be used on retaining rings of various diameters. Optics can be securely fixed in holders without scratching the optics or retaining rings.




Specification		Primary material Shaft: Stainless, Claw: Steel Finish Shaft: None, Claw: Chrome plating				
Part Number	Size Used [mm]	A [mm]	B [mm]			
NRS-50	For φ10 – φ50	50	70			
NRS-100	For φ10 – φ100	100	120			
NRS-150	For φ10 – φ150	150	170			

• The scale on the wrench correlates to the outer diameteter of the lens to be fixed.

Outline Drawing





Application Systems

Optics & Optical Coatings

Opto-Mechanics

Bases

Manual **Stages**

Actuators & Adjusters

Motoeized **Stages**

Light Sources & Laser Safety

Index

Guide

Mirrors

Prisms **Polarizers**

Lasers

Beam Shaping Diffusers

Filters

Shutter Others

Fiber