

This objective lens can be used for laser machining using pulsed laser of SHG (532nm), THG (355nm), and FHG (266nm) YAG laser. Objective lens provides high transmittance at three harmonic wavelengths of YAG.

- With its long working distance and corrected field curvature, its natural observation image is obtained to the periphery of viewing the field.
- It is the long working infinity correction function that is used to introduce a laser system and coaxial observation.
- It allows observation of the sample with visible light (400 – 500nm).
- Laser Damage Threshold (Typical) 0.09 J/cm² (266nm), 0.1J/cm² (355nm), 0.2J/cm² (532nm)
(Laser pulse width 10ns, repetition frequency 20Hz)



Guide

- ▶ Available fixed objective lens holder (LHO-26).
▶ [WEB Reference](#) [Catalog Code](#) W4024
- ▶ When the objective lens is fixed to a 2 axis holder, please consult our Sales Division.
- ▶ For laser processing, we offer a dichoric block (DIMC) and for laser unit with coaxial illumination and observation (OUCI-2).
▶ [WEB Reference](#) [Catalog Code](#) W2041


Attention

- ▶ When an objective lens is used in laser processing, use the diameter of the incident beam to extend to a size of half the pupil diameter ($1/e^2$). A small light spot cannot be achieved when the incident beam is too narrow. Please note if there is a laser energy density increase, there will be a high possibility of damage to the objective lens.
- ▶ The surface of an objective lens can be contaminated by debris during processing. To avoid this, please have sufficient working distance (WD) and insert a thin protective glass on the objective.
- ▶ Magnification is the value when using the imaging lens $f=200\text{mm}$. When used in a microscope lens barrel from other manufacturers there may be different magnifications. The actual magnification should be calculated from the ratio of the focal length of the objective lens and the focal length of the imaging lens to verify the focal length of the imaging lens barrel to be used.


Outline Drawing

(in mm)


PFL-10-UV/NUV-AG




PFL-20-UV/NUV-AG-A



PFL-50-UV/NUV-AG-A



Typical Transmittance Data



Specifications

Part Number	Item name	Magnification	Focal length f [mm]	Numerical aperture NA	Working distance WD [mm]	Resolution ($\lambda=550\text{nm}$) [μm]	Focal depth ($\lambda=550\text{nm}$) [μm]	Real field of view (Eye-piece $\phi 24\text{mm}$)	(Imaging device 1/2-inch)	Weight [kg]
PFL-10-UV/NUV-AG	MPlan UV/NUV 10x	10x	20	0.20	13.5	1.40	± 6.9	$\phi 2.4$	0.48×0.64	0.30
PFL-20-UV/NUV-AG-A	MPlan UV/NUV 20x	20x	10	0.36	15.07	0.76	± 2.1	$\phi 1.2$	0.24×0.32	0.35
PFL-50-UV/NUV-AG-A	MPlan UV/NUV 50x	50x	4	0.42	12.0	0.65	± 1.6	$\phi 0.48$	0.10×0.13	0.41

Compatible Optic Mounts

LHO-26

Application Systems

Optics & Optical Coatings

Opto-Mechanics

Bases

Manual Stages

Actuators & Adjusters

MotORIZED Stages

Light Sources & Laser Safety

Index

Guide

Mirrors

Beamsplitters

Polarizers

Lenses

Multi-Element Optics

Filters

Prisms

Substrates/Windows

Optical Data

Maintenance

Selection Guide

Achromats

Focusing Lenses

f θ Lenses

Objectives

Expanders

Others