

## CHUM-884M/C 8.9MP, 1" CMOS, USB 3.0 Camera

**USB**<sup>™</sup>  
VISION



CHUM-884M/C 8.9 MP 1" CMOS USB 3.0 Camera is a high quality device that can be used in a variety of applications, including electronic semiconductor fabrication, factory automation, bottle inspection and medical packaging.


### Key Features

- Supports auto exposure control, user defined LUT and gamma correction.
- Cameras can be synchronized with hard trigger and soft trigger. Different exposure modes supported.
- Compact structure with the size of 29mm×29mm×30mm, suitable for tight mounting requirement.
- The USB3.0 interface is tightly locked to prevent accidental unplugging and dropping.
- Compatible with USB 3.0 Vision V1.0.


### Application Scenarios

- Electronic semiconductor
- Factory automation
- Bottle inspection
- Medical packaging

### Spectral Response



CHUM-884M Quantum Efficiency



CHUM-884C Quantum Efficiency

### Order Models

Mono: CHUM-884M

Color: CHUM-884C

## Specifications

Model	CHUM-884M	CHUM-884C
Parameters	8.9MP, 1" CMOS, USB 3.0 Camera	
<b>Camera</b>		
Sensor	IMX267	
Pixel Size	3.45μm×3.45μm	
Sensor Size	1"	
Resolution	4096x2160	
Frame Rate	32.2fps	
Dynamic Range	>72.8dB	
SNR	>40dB	
Gain Range	0-20dB	
Exposure Time	50μs-10sec	
Shutter Mode	Global shutter. Auto-exposure, Manual exposure, and One-key exposure	
Data Interface	USB 3.0	
General Purpose I/O	Opto-isolated input x1, Opto-isolated output x1, Bi-directional non-isolated I/O x1	
Image Buffer	128MB	
Data Format	Mono 8/10/10p/12/12p	Mono 8/10/12, Bayer RG 8/10/10p/12/12p, YUV422_YUYV_Packed, YUV422_Packed, RGB8
<b>General</b>		
Power	< 3.27W@12VDC, Voltage 5-15VDC, USB 3.0 power supply supported	
Temperature	Working Temperature 0-50°C, Storage Temperature -30-70°C	
Humidity	20%-80% RH without condensation	
Dimension	44mm×29mm×60mm	
Weight	< 100g	
Lens Interface	C-Mount	
Software	MVS or Third-Party Software supporting USB 3.0 Vision Protocol	
Operating System	Windows XP/7/10 32/64bits	
Compliance	USB 3.0 Vision	
Certification	CE, FCC, RoHS	

### Recommended Accessories

- **Power:** 12VDC @1A power adapter
- **Cable:** Micro USB 3.0 cable (B Type) recommended

### Dimensions

